

Single bossed clamps


with DÄMMGULAST® yellow, hot-dip galvanised

Application


- Suitable for fixings in shipbuilding and industrial areas

Your advantages

- Proven two-part clamp with increased material cross-section
- Connecting thread M10
- Stronger fastening latches in M8 for high load capacity
- Surface protection, thermally hot-dip galvanised
- Lining DÄMMGULAST® yellow, seawater proof
- Average vibration reduction up to 22 dB(A)



Connecting thread M	Size		Clamping range [mm]	Dimensions [mm]			Part no.	Sales unit	Pack unit
	[inch]	[mm]		s	b1	V			
M10	3/8"		14 - 20	2	25	M8 x 30	147958	1	Pieces
	1/2"		20 - 26				147959		
	3/4"		26 - 30				147960		
	1"		32 - 38				147961		
	1 1/4"		40 - 46				147962		
	1 1/2"		48 - 54				147963		
		57	54 - 60				147964		
	2"		60 - 66				147965		
		70	68 - 73				147966		
	2 1/2"		72 - 80				147967		
	3"		88 - 92				147969		
		102	99 - 102				147970		
		110	108 - 112				147971		
	4"		112 - 118				147972		
	125	125 - 130	147973						
5"		137 - 142	147975						
	160	159 - 164	147977						

 These products are manufactured to order. Minimum quantities and delivery time on request.

